



**【注文形式】**



仕様 耐電圧/AC1500V 1分間  
材質 端子部:黄銅(Niメッキ)

**【寸法図】**



**SBRタイプ (各ピッチ丸型端子形状)**

**【寸法表】**

寸法単位(mm)

呼称	P	形式名	極数	A	共通寸法		定格通電電流	販売単位	標準価格(税抜)
7A	7mm	SBR7A-2	2	12.7	W:5.5 M:3.2	t:0.6 D1:20 D2:15.7 D3:4	15A	50	25円
		SBR7A-10	10	68.7				50	106円
		SBR7A-50	50	348.7				50	501円
8A	8mm	SBR8A-2	2	14.5	W:6.5 M:3.8	t:0.6 D1:20 D2:15.7 D3:4	20A	50	25円
		SBR8A-10	10	78.5				50	106円
		SBR8A-50	50	398.5				50	581円
9.5	9.5mm	SBR9.5-2	2	17.4	W:7.9 M:3.7	t:0.6 D1:21 D2:16.7 D3:4	20A	50	28円
		SBR9.5-10	10	93.4				50	110円
		SBR9.5-40	40	378.4				50	431円
10	10mm	SBR10-2	2	18.2	W:8.2 M:4.3	t:0.6 D1:23.2 D2:18.5 D3:6	20A	50	28円
		SBR10-4	4	38.2				50	53円
		SBR10-10	10	98.2				50	112円
		SBR10-20	20	198.2				50	222円

**【当社適合端子台一覧】**

形式	適合端子台
SBR7A-□	PTU-10 PT-SS10 PT-10 PUW-10
SBR8A-□	PTU-20 PT-SS20 PT-20 PUW-20 PTW-SS20 AT-10 CT-15S CT-15 RT-20S CTW-15S2 CTW-15R DT-15
SBR9.5-□	FPS-20H PT-20H
SBR10-□	PTU-30 AT-15L PT-30 RT-30S PUW-30