



【注文形式】



仕様 耐電圧/AC1500V 1分間
 材質 端子部:黄銅(Niメッキ)

【寸法図】



SBRタイプ (各ピッチ丸型端子形状)

【寸法表】

寸法単位(mm)

呼称	P	形式名	極数	A	共通寸法	定格通電電流	販売単位	
7A	7mm	SBR7A-2	2	12.7	W:5.7 M:3.2	t:0.6 D1:20 D2:15.7 D3:4	15A	50
		SBR7A-10	10	68.7				50
		SBR7A-50	50	348.7				50
8A	8mm	SBR8A-2	2	14.5	W:6.5 M:3.8	t:0.6 D1:20 D2:15.7 D3:4	20A	50
		SBR8A-10	10	78.5				50
		SBR8A-50	50	398.5				50
9.5	9.5mm	SBR9.5-2	2	17.4	W:7.9 M:3.7	t:0.6 D1:21 D2:16.7 D3:4	20A	50
		SBR9.5-4	4	36.4				50
		SBR9.5-6	6	55.4				50
		SBR9.5-8	8	74.4				50
		SBR9.5-10	10	93.4				50
10	10mm	SBR9.5-40	40	378.4	W:8.2 M:4.3	t:0.6 D1:23.2 D2:18.5 D3:6	20A	50
		SBR10-2	2	18.2				50
		SBR10-4	4	38.2				50
		SBR10-10	10	98.2				50
		SBR10-20	20	198.2				50

【当社適合端子台一覧】

形式	適合端子台
SBR7A-□	PTU-10 PT-SS10 PT-10 PUW-10
SBR8A-□	PTU-20 PT-SS20 PT-20 PUW-20 AT-10 CT-15S CT-15 RT-20S CTW-15S2 CTW-15R DT-15
SBR9.5-□	FPS-20H PT-20H
SBR10-□	PTU-30 AT-15L PT-30 RT-30S PUW-30