



【注文形式】



仕様 耐電圧/AC1500V 1分間
材質 端子部:黄銅(Niメッキ)

【寸法図】



SBRタイプ (各ピッチ丸型端子形状)

【寸法表】

寸法単位(mm)

呼称	P	形式名	極数	A	共通寸法		定格通電電流	販売単位	標準価格(税抜)
7A	7mm	SBR7A-2	2	12.7	W:5.5 M:3.2	t:0.6 D1:20 D2:15.7 D3:4	15A	50	31円
		SBR7A-10	10	68.7				50	129円
		SBR7A-50	50	348.7				50	608円
8A	8mm	SBR8A-2	2	14.5	W:6.5 M:3.8	t:0.6 D1:20 D2:15.7 D3:4	20A	50	31円
		SBR8A-10	10	78.5				50	129円
		SBR8A-50	50	398.5				50	704円
9.5	9.5mm	SBR9.5-2	2	17.4	W:7.9 M:3.7	t:0.6 D1:21 D2:16.7 D3:4	20A	50	35円
		SBR9.5-10	10	93.4				50	134円
		SBR9.5-40	40	378.4				50	523円
10	10mm	SBR10-2	2	18.2	W:8.2 M:4.3	t:0.6 D1:23.2 D2:18.5 D3:6	20A	50	35円
		SBR10-4	4	38.2				50	65円
		SBR10-10	10	98.2				50	137円
		SBR10-20	20	198.2				50	270円

【当社適合端子台一覧】

形式	適合端子台
SBR7A-□	PTU-10 PT-SS10 PT-10 PUW-10
SBR8A-□	PTU-20 PT-SS20 PT-20 PUW-20 PTW-SS20 AT-10 CT-15S CT-15 RT-20S CTW-15S2 CTW-15R DT-15
SBR9.5-□	FPS-20H PT-20H
SBR10-□	PTU-30 AT-15L PT-30 RT-30S PUW-30